

Mechanical characteristics

cables

interface dimensions acc. to assembly code
 centre conductor
 outer conductor
 mating life
 coupling torque

Components

centre contact
 other metal parts
 insulator
 gasket

Electrical characteristics

impedance
 return loss
 working voltage
 voltage proof
 insulation resistance
 contact resistance
 centre contact
 outer contact

Environmental

operating temp.
 protection class
 RoHS compliant

Mechanische Eigenschaften

Kabel

Steckgesicht nach Montageanleitung
 Innenleiter
 Außenleiter
 Steckzyklen
 Kupplungsdrehmoment

Bauteile

Innenkontakt
 sonstige Metallteile
 Isolierung
 Dichtung

Elektrische Eigenschaften

Wellenwiderstand
 Rückflussdämpfung
 Betriebsspannung
 Prüfspannung
 Isolationswiderstand
 Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung

Betriebstemperatur
 Schutzklasse
 RoHS konform

G 1 (RG-58C/U):
 7806A Belden, 9907 Belden, CNT-195 Andrew, HPF 195 Harbour Industries, KX 15, LMR-195 TMS, RG-58C/U, WCX195 NEK/CDT
 G 5 (RG-223/U):
 RG-223/U, RG-400/U, 1.0/2.95 AF Draka
 RG-141A/U, RG-142B/U

IEC 61169-16
 B03
 solder / Löt
 clamp / Klemm
 >500
 4 - 6 Nm



Materials / Material

brass / Messing
 brass / Messing
 PTFE
 silicone

Finish / Oberfläche

Cu2Ag5
 CuSnZn3

50 Ω
 typ.: 1 GHz -36,5 ; 2 GHz -34,0 ; 3 GHz -30,5 dB
 ≤ 1kV_{eff} / 50 Hz
 2.5 kV_{eff} / 50 Hz
 ≥ 5 GΩ
 ≤ 1.5 mΩ
 ≤ 1.0 mΩ
 -55°C / +155°C
 IP 67 (IEC 60529)
 2002/95/EC

| | | | | | | | | | | |
|------------------|-----------------------------------|-------------|---|------------------------------------|----------------------------|------------|---------------------|--|---|--|
| | | | | 2009 | Datum/ date | Name/ name | Gewicht/ weight (g) | Oberfläche/ surface (mm ²) | Werkstoff/ material | |
| | | | | gez./ drawn | 07.05. | GB | | | | |
| | | | | gepr./ appr. | 12.05.09 | BJ | | | Oberfläche/ finish | |
| | | | | Norm/ stand. | | | | | | |
| | | | Maßstab/ scale | Benennung/ title | | | | |  | |
| | | | 2:1 | N Straight Plug N- Kabelstecker | | | | | | |
| | | | untol. Maße/ dim. without tolerances according to | Untert./doc. type | Zeichnungsnr./ drawing no. | | | | |  Maße/ dimensions: mm |
| | | | K | J01020C1276 | | | | | | |
| Änd./ rev. Index | Änderungsmittelung/ revision code | Datum/ date | Name/ name | Ersatz für/ replaces | | | | | Original : DIN A4 | |
| | | | | J01020B1276 | | | | | Blatt/ sheet 1 von/ of 1 | |