

Außenleiter / outer conductor  
 Innenleiter / inner conductor  
 Isolierung / insulator  
 Crimprohr / crimp ferrule


CuZn39Pb3      Cu2Ni5  
 CuZn38Pb1.5      Cu2Ag5 pas.(INOVAN-SP)  
 PP, POM  
 CuZn38Pb1.5      Cu2Ni5

Kabel / cable

G 7 : KX 22A, KX 3B, RG-174/U (c)  
 RG-188A/U, RG-316/U

Montage / assembly

B2005 (b)

c b a	7710 7317 5077	24.03.97 14.11.96 25.10.94	BI BJ BJ	93	Datum/date	Name/name	Werkstoff/ material	
				gez./drawn	08.06.	JB		
				gepr./appr.	14.06.93	MaH	Oberfläche/ finish	
				Norm/stand.				
Maßstab/scale				Benennung/title				
2:1				FME-Kabelstecker FME-Straight-Plug				
untol. Maße/ dim. without tolerances according to				Untert./doc.type	Zeichnungsnr./drawing no.			
				K	J01700A0007			
Änd./rev. Index				Ersatz für/ replaces				EW930079-00
Änderungsmittlung/ revision code				Datum/ date				 MaßBe/dimensions: mm Original: DIN A4
Name/ name								