

# MC-IC3030 HSPA+ Industrial Computer

## Robust DIN-Rail Fanless Embedded System with Intel® Atom™ Processor

- Fanless design
- Intel® Atom™ Processor
- 2 GB RAM wide temperature
- 16 GB SSD wide temperature
- 4 x RS-232/422/485
- 2 x 10/100/1000 Mbps Ethernet Controller
- HSPA+/UMTS/EDGE/GPRS onboard
- SMA connectors for antenna diversity
- GPS receiver optional
- RTC Battery function
- Power Supply 12V - 24VDC



EN60950



Extended  
Temperature



IP40



Fanless




Low Power

# MC-IC3030 HSPA+ Industrial Computer

## Specifications

- Construction: Extruded aluminum and heavy-duty steel, IP40
- CPU: Intel® Atom™ Processor E3815 1.46GHz
- System: Memory DDR3L-1066 MHz SO-DIMM 2 GB -40°C to +85°C
- BIOS: AMI UEFI BIOS
- Interfaces: Serial Ports 4 x RS-232/422/485 (COM 1-4)  
Select by BIOS  
Supports Auto Flow Control in RS-485 mode
- USB 2 x USB 2.0
- RTC Battery on board
- Storage 1 x SATA SSD 16 GB -40°C to +85°C
- LAN 2 x isolated 10/100/1000 Ethernet ports, no switch
- VGA 1 x DB15 connector
- Power Input 1 x power input 12V-24VDC with terminal block
- Wireless HSPA+/HSPA/UMTS: 850/900/1900/2100 MHz  
EDGE/GPRS/GSM: 850/900/1800/1900 MHz  
1 x SIM socket  
2 x Antenna SMA
- Watchdog Timer: 1 WDT; one step is 1 sec or 1 min 255 levels
- System Indicator: Power, Active
- DC Version: OVP, Reverse protection
- Operating Temperature: -20°C to +70°C
- Storage Temperature: -40°C to +85°C
- Humidity: 5% to 95%
- Vibration Endurance: 2g@5-500Hz, amplitude 0.35mm (operation/storage/transport)
- Weight: 1 kg
- Dimensions: 48 x 110 x 155 mm
- Certification: CE, FCC
- EOS Support: Windows® 7 Embedded  
Windows® 8 Embedded  
Linux/Ubuntu support package
- Scope of delivery: MC-IC3030 System Unit  
Power Terminal Block  
DIN Rail Kit

## Dimensions



## 3G antennas (optional)

### MC0114009-LTE



790- 862 MHz  
890- 960 MHz  
1710-2170 MHz  
2400-2485 MHz  
2500-2690 MHz  
outdoor antenna  
5m Low Loss  
SMA (male)  
incl. bracket

### MC0114027-SMA-ST



850 / 900 MHz  
1800/1900 MHz  
UMTS  
magnetic antenna  
2,5m RG174  
SMA (male)

### MC1213113-SMA-W



850 / 900 MHz  
1800/1900 MHz  
UMTS  
portable antenna  
SMA (male) angle



**MC Technologies GmbH**  
**Kabelkamp 2**  
**30179 Hannover, Germany**

Tel.: +49 (0)511 67 69 99 - 0  
Fax: +49 (0)511 67 69 99 - 150

Web: [www.mc-technologies.net](http://www.mc-technologies.net)  
E-Mail: [info@mc-technologies.net](mailto:info@mc-technologies.net)  
Shop: [www.mct-shop.net](http://www.mct-shop.net)

## Company profile

**We are a leading European provider of innovative solutions for:**

- Machine-to-machine (M2M) hardware and end-to-end solutions
- GSM/GPRS/UMTS/HSPA+/LTE/GPS modules, terminals and router
- Short range modules and solutions
- Customer-specific cable assemblies
- Connectors and assembly groups for industry
- Measuring and inspection technology

**Thanks to our many years of experience we can offer:**

- A broad, attractively priced range of products meeting German quality standards
- Competent technical advice on product selection and design-in
- Quick, professional implementation of all associated commercial and logistical processes
- Comprehensive service concepts for our products and solutions

