

MC SW5

5-port 10/100BASE-TX Industrial Unmanaged Ethernet Switch



The MC SW5 Fast Ethernet Switch offers 5x 10 / 100Mbps Auto-Negotiation RJ-45 ports. All ports support Auto MDI / MDIX function. This feature makes crossover cables or uplink ports redundant. The Switch is Plug & Play and each port can be used as a general port or as an uplink port. The switch is robust and can be fixed on a DIN rail.

- Provides 5-port 10/100BASE-TX
- 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- Power supply: DC Terminal Block power input, 12 to 48V DC
- Power consumption: 2.12W Max.
- Operation temperature: -10°C to 60°C and is tested for functional operation @ -20°C to 70°C
- Storage temperature: -25°C to 85°C
- Casing: Plastic case, IP30
- Dimensions: 26mm (W) x 70mm (D) x 110mm (H)
- Weight: 200g
- Installation: DIN-Rail (Top hat type 35mm)
- Complies with IEC61000-6-2 EMC Generic standard immunity for Industrial environment

Small dimension



DIN-Rail mounting



MC SW5

Industrial Switch

Operation Modes	Access Point, Repeater, Gateway, Wireless ISP, WDS (Wireless Distribution System)
Standard	IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
Frequency Band	2.4 - 2.4835 GHz
Configuration (local and remote)	auto configuration
Network Interfaces	5 LAN; Ethernet 10/100
Power	12-48V, DC over Terminal Block
Operating Temperature	-10°C to 60°C ambient temperature
Storage Temperature	-25°C to 85°C ambient temperature
Humidity	5% to 95% (Non-condensing)
Dimension	H: 110 x W: 70 x L: 27 mm
Weight	0,150 Kg
Mounting	DIN RAIL adapter