

MC Technologies MC89 GPS Terminal

Global 3G with Java™ embedded and GPS



General features:

- Cinterion® EHS8 embedded
- 3GPP Rel.7 Compliant Protocol Stack
- Five Bands UMTS (WCDMA/FDD)
Bands: 800, 850, 900, 1900 and 2100 MHz
- Quadband GSM 850/900/1800/1900 MHz
- SIM Application Toolkit, letter class "b", "c", "e" with BIP and RunAT support
- Control via standardized and extended AT commands (Hayes, TS 27.007 + 27.005)
- TCP/IP stack access via AT command and transparent TCP/UDP services
- Secure Connection with TLS
- Internet Services TCP/UDP server/client, DNS, Ping, FTP client, HTTP client
- Supply voltage range: 8 - 30V
- Operational temperature range: -30 °C to +75 °C
- Dimensions: 65x74x33mm
- Weight: approx. 110g
- DIN rail mounting
- Screw fixing

GPS features:

- Integrated 32 Channel GNSS receiver
- NMEA-183, EGNOS, WAAS
- Position Accuracy (CEP50): 1.5m
- TTFF (-130dBm): 1s Hot Start, <35s Cold Start
- Sensitivity (active antenna):
- Acquisition -145dBm
- Navigation -156dBm
- Tracking -162dBm

Special features:

- USB interface supports multiple composite modes and a Linux-/Mac- compliant mode
- Firmware update via USB and serial interface
- RLS Monitoring (Jamming detection) in 2G and 3G
- Informal Network Scan
- Integrated FOTA, configurable and free of charge
- Hardware watchdog

Java™ Open Platform features:

- Java™ ME 3.2
- Multi-threading programming and Multi-Application execution
- 10 MB RAM and 10 MB Flash File System

Approvals:

- CE, RED
- WEEE, EuP, RoHS and REACH compliant

Specification for data:

- HSDPA Cat.8 / HSUPA Cat.6 data rates
DL: max. 7.2 Mbps, UL: max. 5.76 Mbps
- EDGE Class 12 data rates
DL: max. 237 kbps, UL: max. 237 kbps
- GPRS Class 12 data rates
DL: max. 85.6 kbps, UL: max. 85.6 kbps, Mobile Station Class B
- CSD data transmission up to 9.6 kbps
- SMS text and PDU mode support

Interfaces:

- Power connector 6-pole Western jack
- Mini SIM card reader, 1,8V and 3,0V
- Antenna connector FME (male)
- 2 operating status LED's
- 6 programmable LED's
- USB 2.0 HS interface up to 480 Mbps
- V.24/ V.28 RS-232 interface (D-sub 9-pole female socket) 920kbps, auto bauding

optional:

- **Wireless M-Bus**
- **Digital GPIOs**
- **Any customer specific interface possible**

Driver:

- USB, MUX driver for Microsoft® Windows XP™, Vista™ and 7™
- RIL, USB driver for Microsoft® Windows Embedded Handheld™ >= 6.x
- MUX driver for Microsoft® Windows XP™, Vista™ and 7™

MC Technologies MC89 GPS Terminal und Zubehör

Artikelbezeichnung

MC89 GPS Terminal - Made by MC Technologies -
Netzteil incl. Anschlußleitung / EU-Stecker - auch mit UK- oder US-Stecker lieferbar
Stromkabel / offenes Ende, 6-adrig, ca. 1,5m
12-24V KFZ-Adapter, 1,5m Kabel
Datenkabel 1,8m, 9pol. Stecker - 9pol. Buchse
USB-Standardkabel A/B, 1m
USB-Standardkabel A/B, 2m
12V Akkupack
Hutschienen-Halterung inkl. 2 Befestigungsschrauben

Artikel-Nr.

MC1213889-GPS-TERM
MC1213114-45-EU-N
MC1213115
MC1213116
MC1213226
MC1213229-1
MC1213229-2
MC1213152
Mounting Kit TC/MC




Netzteil



12V Akkupack



USB-Standardkabel



Hutschienen-Halterung (mit Terminal)