

MC0114065-LTE

**Multiband: LTE800/1800/1900/2100/2600,
GSM850/900/1800/1900/ UMTS and WLAN b/g/n**

LTE/GSM/ISM/UMTS/WLAN



Electrical Specifications:

Frequency:	790-869 MHz, 824-894 MHz, 890-960 MHz, 1710-1880 MHz, 1850-1990 MHz, 1920-2170 MHz, 2412-2484 MHz, 2500- 2690 MHz
Impedance:	50 ohm
Polarisation:	Vertical
Gain:	0 dBd, 2.1 dBi
Bandwidth	See „FREQUENCY“
VSWR:	LTE800, GSM850/900 < 2.5:1 LTE1900/1800/2100/2600, GSM1800/1900/UMTS, WLAN b/g/n < 2:1
Max. Power:	40 W



Mechanical Specifications:

Color:	White and chrome
Height:	Approx. 440 mm
Weight:	250 g
Mounting:	On Wall
Mounting place:	On wall or pole with optional bracket
Materials:	PC, PTFE, PE and nickel plated solid brass
Operating temperature:	-40°C to +70°C
Connector:	N-female
Cable:	No cable supplied
Mounting place:	On wall or pole with optional bracket
Ingress Protection:	IP66

