

MC0114065-M-LTE

**Multiband: LTE800/1800/1900/2100/2600,
GSM850/900/1800/1900/ UMTS and WLAN b/g/n**
LTE/GSM/ISM/UMTS/WLAN



Electrical Specifications:

| | |
|---------------|--|
| Frequency: | 790-869 MHz, 824-894 MHz, 890-960 MHz, 1710-1880 MHz, 1850-1990 MHz, 1920-2170 MHz, 2412-2484 MHz, 2500-2690 MHz |
| Impedance: | 50 ohm |
| Polarisation: | Vertical |
| Gain: | 3 dB (Marine), 0 dBd, 2.1 dBi |
| VSWR: | LTE800, GSM850/900 < 2.5:1 LTE1900/1800/2100/2600, GSM1800/1900/UMTS, WLAN b/g/n < 2:1 |
| Max. Power: | 40 W |

Mechanical Specifications:

| | |
|------------------------|--|
| Color: | White and chrome |
| Height: | Approx. 440 mm |
| Weight: | 300 g |
| Mounting: | On 1" threaded pole (G1"-11 thread) with Revolving Nut Kit or on optionally brackets |
| Mounting place: | On mast or deck |
| Materials: | PU-painted glassfibre, PTFE, PE and chromed solid brass |
| Operating temperature: | -40°C to +70°C |
| Connector: | N-female |
| Cable: | No cable supplied |
| Ingress Protection: | IP66 |

